

PA Product

Mini Mixing Amplifier

MPA-603

Double Protection is provided with AC & DC Fuse Circuit. Main Power is shut off if any abnormal state should occur to raise up the current of the circuit . All inputs are mixable



MPA-603

to make the systematic operation. External Mic. Panel plug is available. With treble and bass tone controls. Muting Function is available. The monitoring of audio output signal is available with the Output Level Indicator.



Model:	MPA-603
Power Source:	AC 110/220V 50/60Hz (Internal Jumper Selection)
Power Consumption:	120W
Rated Output Power:	60W
Frequency Response:	50 to 20,000Hz +/-3dB
Distortion:	Less than 0.5% (Rated Output Power at 1 kHz)
Tone Control:	+/- 10dB at 100Hz, 10,000Hz
Input Circuit:	
External Mic. Panel Input	0dB, 10K, Unbalanced With DC 12V Output
Mic. 1, 2	-66dB, 600 Ohms, Unbalanced
AUX 1, 2, 3	-20dB, 10K, Unbalanced
Speaker Output:	4 Ohms, 70V, 100V
Line Output:	0dB, 600 Ohms
Muting Function:	Reduction of Mic 2, Aux 1, 2, 3 Due to Mic. 1 the audio signal supplied from Input Jack No Reduction MIC Input: MIC2
Dimensions (mm):	300(W) x 65(H) x 240(D)
Weight:	6.4kg

*Weight and dimensions indicated above are approximate for reference.

**Specifications are subject to change without notice.