

MS Series

All models out of the MS series designed for

- Excellent sound
- Compact size
- Low weight
- versatile
- Versatile setup combinations

MS-12/1+/MS-12x

The MS-12/1+ is a 2-way full range system in a trapezoidal, computer optimized enclosure. loudspeaker compliment consists of an 12inch lf woofer in a ported sub-enclosure, and a single 1inch compression driver mounted on a 90° x 50° horn. The loudspeaker enclosure shall be rectangular in shape. It shall be constructed of 18mm thickness high density plywood and shall employ extensive internal bracing. Handles are balance-optimized to facility transportation. Perforated steel is employed for frontal protection of the loudspeaker compliment.

MS-15/1+/MS-15x

The MS-15/1+ is a 2-way full range system in a trapezoidal, computer optimized enclosure. loudspeaker compliment consists of an 15inch lf woofer in a ported sub-enclosure, and a single 1inch/2inch compression driver mounted on a 90° x 55° horn. The loudspeaker enclosure shall be rectangular in shape. It shall be constructed of 18mm thickness high density plywood and shall employ extensive internal bracing, daddo for strength and durability. Handles are balance-optimized to facility transportation. perforated steel is employed for frontal protection of the loudspeaker compliment.



MS-12x
Full Range




MS-15/1+
Full Range



MS-12/1+
Full Range



MS-15x
Full Range



MS Series

Model:

System Power Rating
Frequency Range(±3dB)
Impedance
Sound Pressure Level(1w/1m)/max.cont.
Coverage (H x V)
Transducers LF

M/HF
Dimensions w x h d (inch)
w x h d (millimetre)
Weight (Kg)
Connectors

MS-12x

300W AES, 1200w Peak
55Hz-20KHz
8ohm
99dB/129dB SPL
90° x 50°
12inch cone Drivers
1inch Throat Driver
14.17x24.21x13.78
360x615x350
21
2 x Neutrik NL4 Speaker

MS-12/1+

250W AES, 1000w Peak
55Hz-20KHz
8ohm
98dB/128dB SPL
90° x 50°
12inch cone Drivers
1inch Throat Driver
14.17x24.21x13.78
360x615x350
21
2 x Neutrik NL4 Speaker

MS-15x

350W AES, 1400w Peak
50Hz-20KHz
8ohm
100dB/133dB SPL
90° x 55°
15inch cone Drivers
2inch Throat Driver
16.93x27.48x14.49
430x698x368
26
2 x Neutrik NL4 Speaker

MS-15/1+

350W AES, 1400w Peak
50Hz-20KHz
8ohm
100dB/133dB SPL
90° x 55°
15inch cone Drivers
1inch Throat Driver
18.82x37.71x22.06
478x780x535
36
2 x Neutrik NL4 Speaker

Specifications

MS Series

MS System applications


- portable And Installed A/V
- front Fill
- Under Balcoony Fill
- Surround Sound Presentations
- Sistributed Systems
- Ultra Compact With Very High Output

MS-15/2+

A Dual way full range system: The MS-15/2+ is a Dual way full rang system in a trapezoidal, computer optimized enclosure. loudspeaker compliment consists of an Dual 15inch lf woofer in a ported sub-enclosure, and a single 2inch compression driver mounted on a 55° x 90° horn. The loudspeaker enclosure shall be rectangular in shape. It shall be constructed of 18mm thickness high density plywood and shall employ extensive internal bracing. daddoe f or strength and durability. Handles are balance-optimized to facilitate transportation. Perforated steel is employed for frontal protection of the loudspeaker compliment.



MS-15/2+
Full Range




MS-215B

A dedicated subwoofer with Dual 15inch transducers: The MS-215B is a dedicated LF/subwoofer system, computer optimized enclosure. Loudspeaker compliment consists of a dual 15 inch LF woofer in a vented chamber. The loudspeaker enclosure shall be rectangular in shape. It shall be constructed of 18mm thickness high density plywood and shall employ extensive internal bracing. Daddoe f or strength and durability. Handles are balance-optimized to facilitate transportation. a standard tripod/polemount adaptor is included. perforated steel is employed for frontal protection of the loudspeaker compliment.




MS-215B
Bass



MS-180Bx

A dedicated subwoofer with Singal 18inch transducers: The MS-180Bx is a dedicated LF/subwoofer system, computer optimized enclosure. Loudspeaker compliment consists of a single 18 inch LF woofer in a vented chamber. The loudspeaker enclosure shall be rectangular in shape. It shall be constructed of 18mm thickness high density plywood and shall employ extensive internal bracing. Daddoe f or strength and durability. Handles are balance-optimized to facilitate transportation. a standard tripod/polemount adaptor is included. perforated steel is employed for frontal protection of the loudspeaker compliment.

MS-180Bx
Bass



MS Series

Specifications

Model:

System Power Rating
Frequency Range(±3dB)
Impedance
Sound Pressure Level(1w/1m)/max.cont.
Coverage (H x V)
Transducers LF
M/HF
Dimensions woxhd(Inch)
waxhd(millimetre)
Weight(Kg)
Connectors

MS-15/2+

600W AES,2400w Peak
45Hz-20KHz
4ohm
101dB/137dB SPL
55° x 90°
2x15inch cone Drivers
2inch Throat Driver
18.82x44.69x22.06
478x135x535
52
2 x Neutrik NL4 Speakon

MS-215B

800W AES,3200w Peak
35Hz-200Hz
4ohm
101dB/126dB SPL

2x15inch cone Drivers

42.52x18.50x22.06
1080x470x635
66
2 x Neutrik NL4 Speakon

MS-180Bx

450W AES,1800w Peak
35Hz-350Hz
8ohm
102dB/138dB SPL

18inch cone Drivers

22.05x21.26x37.7
560x540x780
49
2 x Neutrik NL4 Speakon