

MINI LED MOVING HEAD (SPOT)

MODEL : MINISPOT 150

The MINISPOT 150 features a 7500K 150W LED with high intensity and efficiency. It produces very high light output, through a specific 13.2° optic system. The PAN/TILT integrates in fast and quiet movement. It offers a full complement of professional characteristics, including a rotating gobo wheel, static gobo wheel, color wheel, a 3-facet prism, linear electronic focus, 0-100% linear LED dimmer, variable speed shutter/strobe.



Product Features:

- A 150W white LED lamp, 7500K
- 50000 hours life span and low power consumption
- 8/16 bit smooth and precise resolution for PAN/TILT movement
- 360°/540°/630° PAN and 90°/180°/270° TILT movement
- PAN/TILT inversion available
- Scan position memory, auto reposition after unexpected movement
- Specific high precision glass optic system with 13.2° projection angle
- Improved optics and flat beam field
- 1 Rotatable gobo wheel with 6 rotatable an interchangeable gobos plus open with speed adjustable, stream effect, dithering effect and rotatable clockwise or anticlockwise
- Gobo size 24mm (external)/13.5mm (inner)
- Static gobo wheel with 11 gobos plus open
- Color wheel with 7 colors plus open
- Variable direction rainbow effect with speed adjustable
- 2.5m-15m electric focus
- 3-Facet prism with variable speed and direction
- 0-100% Smooth linear LED dimmer
- Preset variable/random strobe and dimming pulse effect
- 25T/sec high speed LED shutter/strobe effect with variable speed
- 12/14/16 DMX channels USITT DMX-512
- DMX512, master-slave, and sound activated controllable or auto operation (7 built-in programs)
- Blue LCD display
- POWRECON connector IN/OUT
- 3-Pin XLR connectors IN/OUT
- Low noise fan cooling system
- Constant temperature readout and management function
- -20°C ~ 45°C max ambient temperature
- IP20 protection rating
- 2*1/4 turn fastening Omega clamp
- 1* Safety attachment point

Specification:

Input Voltage: AC90-260V 50/60Hz
LED Source: 1 x 150W white LED
Power Consumption: 215W
Dimensions: 183(D)*298(W)*410(H)MM
Packing Dimensions: 380(D)*280(W)*505(H)mm
Net Weight: 10.38kg
Gross Weight: 12.56kg

PHOTOMETRIC BEAM ANGLE DATA (FC=LUX x 0.0929)

