

AUDIO-VISUAL STATION



Solid State / Dual Digital Player & Recorder with Audio / Video

DMP-3R

Overview

The AVS DMP-3R is designed to fulfill the most demanding playback and recording applications in AV installation, audio production, live sound, theatre and broadcast. DMP-3R is an up to date replacement for cassette, MD, DAT, CDR and commodity PC based systems currently fulfilling such roles.

Besides, DMP-3R supports RS-232 remote control, users may perform various operation and control from host device.



Feature :

- * 1 U Rackmount size for easy installation
- * RS-232 UART connection supported, can be operated and controlled by remote host
- * Up to date replacement for cassette, DAT, MD, CDR and PC based system
- * Records and plays back from stable, industry-standard SD/SDHC flash media and USB Thumb
- * Supported Audio formats : MP3 and WMA
- * Supported Video formats : AVI, MP4, MPG, VOB, DAT
- * Supported Still Image formats : JPG
- * Support up to 16GB USB Thumb / SD Card / SDHC
- * Recording format : MP3 at 44.1 KHz / Bit rate : 128kbps or 192kbps
- * Recording media : USB Thumb or SD Card/SDHC*
- * Various play back modes (single, continuous, repeat and random)
- * Play back volume control
- * Support CD/VCD/DVD
- * Component Video Out x 1
- * Video Out x 2 (1 in Front panel, 1 in Rear panel)
- * AUX IN : Connect to other music source



SD/SDHC/USB Thumb supported



Slide in CD/VCD/DVD design. Support various Media Codecs

* Specifications and design are subject to change without notice

Email : marketing@avshk.com

Website : <http://www.avshk.com>

AUDIO-VISUAL STATION



Solid State / Dual Digital Player & Recorder with Audio / Video

DMP-3R



Specifications - Card Reader & Recorder

System - Recording

- Recording media : SD/SDHC or USB Thumb up to 16GB
- Recording format : MP3 - MPEG1 Layer III audio
- Recording MP3 bitrate : 128kbps, 192kbps
- Sampling frequency : 44.1KHz

Audio Section

- Audio Channels : 2 (Stereo)
- Frequency Response : 20 Hz ~ 40kHz ± 1.0 dB
- Sampling frequency : 44.1KHz
- S/N Ratio : 96 db (1kHz)

Inputs & Output

- REC IN : 1 x RCA Type
- AUX IN : 1 x 3.5mm (Front Panel)
- AUDIO OUT : 1 x RCA Type

RS-232 Controls

- RS-232 UART terminal : 9 Pin D-sub (Female connector)

Specifications - CD/VCD/DVD & Card Reader

System - Playback

- Media Support : CD/DVD/VCD, SD/SDHC or USB Thumb up to 16GB
- Video Codec : Divx3.11/Divx4.X/Divx5.X/Divx Pro Xvid, MPEG 4, MPEG2, MPEG1
- Audio Formats : MP3, WMA
- Still Images : JPEG

Inputs & Outputs

- AUDIO OUT : 1 x RCA
- AUX IN : 1 x 3.5mm
- VIDEO OUT : x 2 (Front x 1, Rear x 1)
- COMPONENT VIDEO OUT : x 1

Other Information

- Power Supply : AC 230V, 50Hz
- Operating Temperature :
- Dimensions : Standard 1U rack mount
: 485mm(W) x 48 mm(H) x 285mm(D)
- Weight : 3.9 Kg



* Specifications and design are subject to change without notice

Email : marketing@avshk.com

Website : <http://www.avshk.com>