

#### All models out of the DS Series designed for

- -Low weight
- -versatile -Versatile setup combination s



## DS-118B


A dedicatded subwoofer with 18inch transducers. Loudspeaker compliment consists of a 18inch(100mm voice coil) ferrite magnet LF woofer in a vented chamber. The loudspeaker enclosure shall be rectangular in shape. It shall be constructed of 18mm thickness high density plywood and shall employ extensive internal bracing. It shall be finished in wear-resistant textured black paint, adopted for strength and durability. Handles are balance-optimized to faciliate transportation. A standard tripod/polemout adaptor is included. Perforated steel is employed for frontal protection of the loudspeaker compliment.


### DS-128B

A dedicatded subwoofer with 18inch transducers. Loudspeaker compliment consists of dual 18inch(100mm voice coil) ferrite magnet LF woofer in a vented chamber. The loudspeaker enclosure shall be rectangular in shape. It shall be constructed of 18mm thickness high density plywood and shall employ extensive internal bracing. It shall be finished in wear-resistant textured black paint, adopted for strength and durability. Handles are balance-optimized to faciliate transportation. A standard tripod/polemout adaptor is included. Perforated steel is employed for frontal protection of the loudspeaker compliment.



**DS-118B** Bass







**DS-128B** Bass

#### DS Series

#### Model:

System Power Rating Frequency Range(±3dB)

Impedance

Sound Pressure Level(1w/1m)/max.cont.

Coverage

Transducers LF M/HF

Dimensions wxhxd(inch)

wxhxd(millimetre)

Weight(Kg) Connectors

# DS-118B

450w AES, 1800w Peak 40Hz-350Hz

99dB/133dB SPL

18inch Bass Driver

22x26.77x27.6 560x680x770

2 x Neutrik NL4 Speakon

#### DS-128B

900w AES,3600 Peak 38Hz-350Hz 40hm 102dB/138dB SPL

2x18inch Bass Driver

40.96×26×22.16 1040x650x560

2 x Neutrik NL4 Speakon

