



Specifications

Light Source: 1x270W LED
 Color Temperature: 8000K
 Beam Angle: 8°~45°

Features

Linear motorized zoom with wash effect, zoom range: 8°~45°
 Motorized focus
 Linear CMY color mixing
 Color Wheel: 1 color wheel with 9 colors plus open
 Gobo Wheel: 1 static gobo wheel with 9 gobos plus open
 1 rotating gobo wheel with 7 gobos plus open, easy to replace
 Gobo's outside diameter: 26.8mm
 Gobo's image diameter: 19mm
 Motorized linear iris
 3 facet prism rotating in both directions
 Independent frost effect
 Various strobe speeds

ENERGY SPOT PRO KA-400 SPOT PRO

Control

DMX Channel: 18/22/25 channels
 Control Mode: DMX512
 Firmware Upgrade: Update via DMX link&USB

Pan/Tilt

Pan/Tilt: 540°/ 270°
 Pan/Tilt Resolution: 16 bit


Construction

Display: LCD display
 Data In/Out: 3-pin and 5-pin XLR
 Power In/Out: PowerCon in/out
 Protection Rating: IP20


Electrical and Physical

Power Voltage: AC 100~240V, 50/60Hz
 Power Consumption: 420W
 Dimensions: 369x253x625mm
 Weight: 20Kg

Photometrics Diagram




Dimensions(mm)




CMY/Color/Gobo Wheel




CMY



Color Wheel



Static Gobo Wheel



Rotating Gobo Wheel